



SOLIDEAL XTREME

TIRE SIZE	RIM SIZE ⁽¹⁾	TREAD PATTERN	HEEL		ACTUAL TIRE DIMENSIONS				WEARABLE HEIGHT		LOAD CAPACITY ⁽²⁾ • Counterbalanced lift trucks			
					Overall diameter		Overall width				Load wheel		Steering wheel	
			Normal	Quick	mm	inch	mm	inch	25 km/h • 16 mph		25 km/h • 16 mph			
									kg	lbs	kg	lbs		
5.00 - 8	3.00D - 8	XTR	■	■	450	17.7	122	4.8	39	1.5	1415	3100	1090	2400
15 x 4 1/2 - 8	3.00D - 8	XTR	■	■	376	14.8	114	4.5	28	1.1	1040	2300	800	1750
16 x 6 - 8	4.33R - 8	XTR	■	■	412	16.2	150	5.9	34	1.3	1495	3300	1150	2550
18 x 7 - 8	4.33R - 8	XTR	■	■	451	17.8	153	6.0	46	1.8	2145	4750	1650	3650
6.00 - 9	4.00E - 9	XTR	■	■	524	20.6	138	5.4	52	2.0	1885	4150	1450	3200
21 x 8 - 9	6.00E - 9	XTR	■	■	519	20.4	187	7.4	49	1.9	2755	6100	2120	4700
140/55 - 9	4.00E - 9	XTR		■	377	14.8	130	5.1	28	1.1	1170	2600	900	2000
6.50 - 10	5.00F - 10	XTR	■	■	566	22.3	162	6.4	55	2.2	2340	5150	1800	3950
180/60 - 10	5.00F - 10	XTR		■	452	17.8	160	6.3	33	1.3	2405	5300	1850	4100
23 x 9 - 10	6.50F - 10	XTR	■	■	583	23.0	204	8.0	52	2.0	3445	7600	2650	5850
200/50 - 10	6.50F - 10	XTR	■	■	461	18.1	191	7.5	35	1.4	2470	5450	1900	4200
7.00 - 12	5.00S - 12	XTR	■	■	650	25.6	168	6.6	63	2.5	2920	6450	2240	4950
23 x 10 - 12	8.00G - 12	XTR	■	■	586	23.1	234	9.2	45	1.8	3770	8300	2900	6400
27 x 10 - 12	8.00G - 12	XTR	■	■	680	26.6	244	9.6	64	2.5	3900	8600	3000	6600
7.00 - 15	5.50 - 15	XTR	■	■	729	28.7	179	7.0	60	2.3	3545	7850	2725	6000
7.00 - 15	6.00 - 15	XTR	■		729	28.7	179	7.0	60	2.3	3545	7850	2725	6000
7.50 - 15	5.50 - 15	XTR	■	■	752	29.6	199	7.8	62	2.4	3900	8600	3000	6600
7.50 - 15	6.00 - 15	XTR	■	■	752	29.6	199	7.8	62	2.4	3900	8600	3000	6600
7.50 - 15	6.50 - 15	XTR	■	■	752	29.6	199	7.8	62	2.4	3900	8600	3000	6600
8.25 - 15	6.50 - 15	XTR	■	■	813	32.0	212	8.3	72	2.8	4750	10500	3650	8050
28 x 9 - 15	7.00 - 15	XTR	■	■	687	27.0	218	8.6	54	2.1	3770	8300	2900	6400
28 x 12.5 - 15 (355/45 - 15)	9.75 - 15	XTR	■	■	689	27.1	291	11.5	46	1.8	5525	12200	4250	9400
250 - 15	7.00 - 15	XTR	■	■	719	28.3	225	8.9	62	2.4	4750	10500	3650	8050
250 - 15	7.50 - 15	XTR	■	■	719	28.3	225	8.9	62	2.4	4750	10500	3650	8050
300 - 15	8.00 - 15	XTR	■	■	815	32.1	257	10.1	75	3.0	5850	12900	4500	9950
355/65 - 15	9.75 - 15	XTR	■	■	819	32.2	312	12.3	75	2.9	7800	17200	6000	13250
10.00 - 20	7.00 - 20	XTR	■		1035	40.7	255	10.0	82	3.2	6000	13250	5000	11050
10.00 - 20	7.50 - 20	XTR	■	■	1035	40.7	255	10.0	82	3.2	6000	13250	5000	11050
10.00 - 20	8.00 - 20	XTR	■	■	1035	40.7	255	10.0	82	3.2	6000	13250	5000	11050
12.00 - 20	8.00 - 20	XTR	■		1090	42.9	283	11.1	88	3.4	7560	16700	6300	13900
12.00 - 20	8.50 - 20	XTR	■		1090	42.9	283	11.1	88	3.4	7560	16700	6300	13900
12.00 - 20	10.00 - 20	XTR	■		1090	42.9	283	11.1	88	3.4	8520	18800	7100	15650